

TRX 5X2

Unit mounted on Rubber Chermack Tracks with a 99 HP Kubota Turbo Diesel Engine

- Tracks are 18" Wide x 107" Long
- 5,000 lb Single Line or 10,000 lb Double Line
- Main and Sand Lines along with Structure are Tested and Certified with Dynamometer
- Parker Proportional Electric over Hydraulic System
- Built-in PTO and Pump
- Custom HD 100" x 144" Diamond Plate Flatbed
- Custom Headache Rack
- Complete Wireless Remote Operation or Hands On
 - The Remote Controls Tracks, Mast, Throttle, Main and Sand Line Winches from up to 200 feet away
- Electric over Hydraulic Controls for Winches, Mast, Mast Extension, & Outriggers
- 34-foot extendable MAST
 - With 32-feet of True Hook Height
 - 2 LED Light Bars on Mast
- 60 Gallon Hydraulic Oil Tank
- 25 Gallon Diesel Tank
- Hydraulic Oil Cooler with Thermostat Control
- 2 Built-In Toolboxes in Bed
 - 64" long x 7.5" wide x 8" deep
- Variable Speed Main and Sand Line with Dual Safe Brakes
 - Main Line pulls at 250 fpm/5000 lb.
 - Sand Line pulls at 1850 fpm/500 lb.
- Enclosed Control Panel
 - Electronic Weight Indicator
 - Electronic Oil Pressure Gauge
 - Electronic Oil Temperature with Auto Hi Temp Shutdown
 - Electronic Oil Filter Service Indicator
 - PTO Hour Indicator
- 4 Hydraulic Outriggers with 24" Stroke & 12" Base
- 2 LED Headlights Bars
- Dual 4"x 96"x 2.25" Hydradyne Hydraulic Cylinders
- 4"x 96"x 2.25" Hydraulic Mast Extension Cylinder
- Dupont Imron 2-part Industrial Paint