

24X3

Large Unit mounted on Kenworth T-370

- 24,000 lb. Single Line or 48,000 lb. Double Line or 72,000 lb. Triple Line
- Main and Sand Lines along with Structure are Tested and Certified with Dynamometer
- Parker Proportional Electric over Hydraulic System
- Automatic Transmission PTO and Pump Installation
- Custom HD 8'6" x 17' Diamond Plate Flatbed
- Custom Headache Rack above Deck
- Remote (Optional)
 - Controls Mast, Throttle, Main and Sand Line Winches from up to 300 feet Away
- Electronic over Hydraulic Controls for Winches, Mast, Mast Extension, Outriggers, & Layout Lines
- 53-foot Extendable MAST
 - With 51 feet of True Hook Height
- Dual Hydraulic Swing Arms
- Dual Custom Mud flaps

UPGRADES

- Elevator Storage Cage
 - 8' x 30" x 30"
 - These Cages are Custom Designed and Manufactured by TDH Manufacturing

- Variable Speed Main and Sand Line with Dual Safe Brakes
- Main Line Pulls at 181 fpm/18,000 lb.
 - 250' 5/8" cable
- Sand Line Pulls at 490 fpm/5000 lb.
- Dual Layout Line Winches
 - 250 fpm/ 3000 lb.
 - 250' 3/8" cable
- Enclosed Control Panel
 - Electronic Oil Pressure Gauge
 - Electronic Oil Temperature
 - Electronic Oil Filter Service Indicator
- 4 Hydraulic Outriggers with 24" Stroke 12" Base
- 125 Gallon Hydraulic Tank
- Hydraulic Cooler with Thermostat Control
- Over 136 Sqft of Open Deck Space
- LED Lights on Truck Bed
- Heavy Duty Rear Bumper with Curt Receiver Hitch
- Dual 5.5"x 120"x 4" Hydraulic Cylinders
- Dual 5.5"x 180"x 4" Hydraulic Mast Extension Cylinder
- Dupont Imron 2-part Industrial Paint