

35X4

Largest Unit Mounted on Kenworth T-880

- 35,000 lb Single Line or 70,000 lb Double Line or 105,000 lb Triple Line or 140,000 lb Quad Line
- Main and Sand Lines Along with Structure are Tested and Certified with Dynamometer
- Parker Proportional Electric over Hydraulic System
- Automatic Transmission PTO and Pump Installation
- Custom HD 8'6" x 22' Diamond Plate Flatbed
- Custom Headache Rack Above Deck
- Remote (Optional)
 - Controls Mast, Throttle, Main and Sand Line Winches from up to 300 feet Away
- Electronic over Hydraulic Controls for Winches, Mast, Mast Extension, Outriggers, & Layout Lines
- 58-foot Extendable MAST
 - With 55 feet of True Hook Height
- Dual Hydraulic Swing Arms
- Dual Custom Mud Flaps

UPGRADES

- Elevator Storage Cage
 - 8' x 30" x 30"
 - These Cages are Custom Designed and Manufactured by TDH Manufacturing

- Variable Speed Main and Sand Line with Dual Safe Brakes
- Main Line Pulls at 180 fpm/35,000 lb.
 - 300' 7/8" cable
- Sand Line Pulls at 520 fpm/8000 lb.
- Dual Layout Line Winches
 - 220 fpm/ 3000 lb.
 - 250' 3/8" cable
- Enclosed Control Panel
 - Electronic Oil Pressure Gauge
 - Electronic Oil Temperature
 - Electronic Oil Filter Service Indicator
- 4 Hydraulic Outriggers with 24" Stroke 16" Base
- 125 Gallon Hydraulic Tank
- Hydraulic Cooler with Thermostat Control
- Over 176 Sqft of Open Deck Space
- LED Lights on Truck Bed
- Heavy Duty Rear Bumper with Curt Receiver Hitch
- Dual 6" x 180" x 4" Hydraulic Cylinders
- Dual 6" x 180" x 4" Hydraulic Mast Extension Cylinder
- Dupont Imron 2-part Industrial Paint