

7X3

Mid Size Unit mounted on Ford F550 with 84" c/a and a 6.7 liter Diesel

*Optional configuration based on customer specs

- 7,000 lb. Single Line or 14,000 lb. Double Line or 21,000 lb. Triple Line
- Main and Sand lines along with Structure are tested and certified with Dynamometer
- Parker Proportional electric over hydraulic system
- Automatic Transmission PTO and Pump Installation
- Custom HD 8'4" x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- Pistol Grip Wireless Remote*
 - Controls Mast, throttle, Main and Sand line Winches from up to 300 feet away
- Electronic over Hydraulic Controls for Winches, Mast, Mast Extension, Outriggers & Pipe Racks
- 47-foot extendable MAST
 - With 45 feet of True Hook Height
- Dual Hydraulic Tilting Pipe Rack with Pipe securing winches
- Sand Line Counter*
 - Shows IN FEET & INCHES depth of Sand line cable in hole.
- Auxiliary Hydraulics with quick connects in rear*
 - Can connect generator, breakout cylinder, spinner or anything else that may need power
- Weight Load Indicator*
 - Shows weight in lbs. ON HOOK
- Dual custom Mud flaps
- Variable Speed Main and Sand line with dual safe brakes
- Main line pulls at 250 fpm/7000 lb.
 - 250' 1/2" Cable w/3t. tapered roller thrust bearing Crosby Hook
- Sand line pulls at 500 fpm/ lbs.*
 - Holds 1,000' of 3/8" cable
- Enclosed Control Panel
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - PTO Hours
- Hydraulic Outriggers with 24" stroke 12" base
- 50 Gallon Hydraulic Tank
- Hydraulic cooler with thermostat control
- Over 90 Sqft of Open Deck Space
- LED Lights on truck bed
- Heavy duty Rear bumper with Curt receiver hitch
- Dual 4"x96"x2.25" Hydrodyne hydraulic cylinders
- 4"x180"x2.5" Hydraulic mast extension cylinder
- Dupont Imron 2-part industrial paint
- JOMAC Mounted Utility Boxes*
 - JOMAC 120"x32"x20" 5 compartments
 - JOMAC 72"x32"x20" 3 compartments
 - These service body sides are custom designed by TDH and manufactured by JOMAC