

4X3

Small Unit mounted on Flatbed or Utility Body

*Optional configuration based on customer specs

- 4,000 lb. Single Line or 8,000 lb. Double Line or 12,000 lb. Triple Line
- Main and Sand lines along with Structure are tested and certified with Dynamometer
- Parker Proportional Valve System
- Automatic Transmission PTO and Pump Installation*
- Custom HD 8' x 10' Diamond Plate Flatbed*
 - Custom Headache rack above deck
- Wireless Remote
 - Controls Main Line with Variable Speed
- 40-foot MAST
 - Optional Extension up to 48'*
- Dual Hydraulic Tilting Pipe Rack with Pipe securing winches*
- Auxiliary Hydraulics with quick connects in rear*
 - Can connect generator, breakout cylinder, spinner or anything else that may need power
- Dual custom Mud flaps
- LED Lights on truck bed
- Heavy duty Rear bumper with Curt receiver hitch

- Variable Speed Main and Sand line
- Main line pulls at 250 fpm/4000 lb.
 - 250' 3/8" Cable w/3t. tapered roller thrust bearing Crosby Hook
- Sand line pulls at 550 fpm/1000 lbs.*
 - Holds 1,000' of 5/16" cable
- Dual Hydraulic Outriggers with 24" stroke 12" base
- 35 Gallon Hydraulic Tank
- Hydraulic cooler with thermostat control
- Dual 3"x96"x2" Hydraulic Mast Raise Cylinder
- 3.5"x120"x 2.5" Hydraulic mast extension cylinder*
- Dupont Imron 2-part industrial paint
- JOMAC Mounted Aluminum Utility Boxes*
 - JOMAC 120"x32"x20" 5 compartments
 - JOMAC 72"x32"x20" 3 compartments
 - These service body sides are custom designed by TDH and manufactured by JOMAC
- Knapheide Tip-Top Service Body*
 - 11' long sealed locking boxes
- Electric Over Hydraulic Upgrade*
 - Weight Load Indicator
 - Sand Line Speed Control
 - PTO/Throttle control from rear