

30X4 Specs

Mounted on Flatbed

Standard Features

- 120,000 lb. Hook load on 4-part block
 - Variable Speed Main & Sand line
 - Main & Sand line along with structure are tested and certified with Dynamometer
 - NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/30,000 lbs.
 - Supplied with 280' of 3/4" cable & 15t hook
- 55 ft hydraulically extending MAST
 - 53' of True Hook Height
 - Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 20' Diamond Plate Flatbed
- Custom Headache rack above deck
- 125 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 4-Part Block

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 3500 lb. -- holds 2500' of 1/2" Cable
 - 5000 lb. -- holds 3500' of 1/2" Cable
 - 8000 lb. -- holds 4000' of 5/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Layout Line winches -- available on driver and/or passenger side
 - 250 fpm/2000 lb. -- 150' 3/8" Cabel
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Cathead with rollers
- Sargent GEN 2 Spinner
 - 2-12" Pipe
 - Heavy Duty Clamp