

35X4 Specs

Mounted on Flatbed

Standard Features

- 140,000 lb. Hook load on 4-part block
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 210 fpm/35,000 lbs.
- Supplied with 280' of 7/8" cable & 20t hook
- 58 ft hydraulically extending MAST
- 55' of True Hook Height
- Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 20' Diamond Plate Flatbed
- Custom Headache rack above deck
- 125 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 4-Part Block

Additional Options

- Sand Line Options -- All 550 fpm bare drum
- 3500 lb. -- holds 2500' of 1/2" Cable
- 5000 lb. -- holds 3500' of 1/2" Cable
- 8000 lb. -- holds 4000' of 5/8" Cable
- Adjustable speed settings
- Available counter that shows DEPTH in INCHES
- Layout Line winches -- available on driver and/or passenger side
- 250 fpm/2000 lb. -- 150' 3/8" Cabrel
- Electric over Hydraulic Upgrade
- Electronic oil pressure gauge
- Electronic oil temperature
- Electronic oil filter service indicator
- Weight Load Indicator in LBS.
- Wireless Remote
- Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
- Sealed airtight with locks
- GETEC Hydraulic Generator
- 120V/14,000 Watts
- Hydraulic Air Compressor
- 17 CFM
- Auxiliary Hydraulics/Breakout Cylinder
- Rhino Line
- Cathead with rollers
- Sargent GEN 2 Spinner
- 2-12" Pipe
- Heavy Duty Clamp