

# 6X2 Specs

## Mounted on Flatbed or Service Body

### Standard Features

- 12,000 lb. Hook load on 2-part line (block NOT Included)
- 3-Part option to pull up to 18,000 lbs.
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/6,000 lbs.
- Suppled with 250' of 7/16" cable & 3t hook
- 40 ft hydraulically extending MAST
- Optional Extension up to 48'
- Standard 20 ft aluminum pipe racks with pipe securing winches
- Hydraulic lowering option available
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- 50 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint

### Additional Options

- Sand Line Options -- All 550 fpm bare drum
  - 1000 lb. -- holds 1000' of 3/8" Cable
  - 1500 lb. -- holds 1500' of 3/8" Cable
  - 2500 lb. -- holds 2000' of 3/8" Cable
  - Adjustable speed settings
  - Available counter that shows DEPTH in INCHES
- Electric over Hydraulic Upgrade
  - Electronic oil pressure gauge
  - Electronic oil temperature
  - Electronic oil filter service indicator
  - Weight Load Indicator in LBS.
  - Wireless Remote
    - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
  - Sealed airtight with locks
- GETEC Hydraulic Generator
  - 120V/14,000 Watts
- Hydraulic Air Compressor
  - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Hybrid Option Available
- Front Outrigger & Wire Winder options
- 2 Part Block and 7 Ton hook