



Product Catalog

3X2



3-TON PUMP HOIST

3X2 Specs

Mounted on Flatbed or Service Body

Standard Features

- 6,000 lb. Hook load on 2-part line (block not included)
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/3,000 lbs.
- Suppled with 175' of 3/8" cable & 3t hook
- 40 ft hydraulically extending MAST
 - Optional Extension up to 48'
- Standard 20 ft aluminum pipe racks with pipe securing winches
 - Hydraulic lowering option available
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- 50 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 1000 lb. -- holds 1000' of 3/8" Cable
 - 1500 lb. -- holds 1500' of 3/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Hybrid Option Available
- Front Outrigger & Wire Winder options
- 2 Part Block

4X3



6-TON PUMP HOIST

4X3 Specs

Mounted on Flatbed or Service Body

Standard Features

- 12,000 lb. Hook load on 3-part line (block NOT included)
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/4,000 lbs.
- Suppled with 250' of 3/8 cable & 3t hook
- 40 ft hydraulically extending MAST
 - Optional Extension up to 48'
- Standard 20 ft aluminum pipe racks with pipe securing winches
 - Hydraulic lowering option available
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- 50 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 1000 lb. -- holds 1000' of 3/8" Cable
 - 1500 lb. -- holds 1500' of 3/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Hybrid Option Available
- Front Outrigger & Wire Winder options
- 3-Part Block and 7 Ton hook

6X2



6-TON PUMP HOIST

6X2 Specs

Mounted on Flatbed or Service Body

Standard Features

- 12,000 lb. Hook load on 2-part line (block NOT Included)
- 3-Part option to pull up to 18,000 lbs.
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/6,000 lbs.
- Supplied with 250' of 7/16" cable & 3t hook
- 40 ft hydraulically extending MAST
- Optional Extension up to 48'
- Standard 20 ft aluminum pipe racks with pipe securing winches
- Hydraulic lowering option available
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- 50 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 1000 lb. -- holds 1000' of 3/8" Cable
 - 1500 lb. -- holds 1500' of 3/8" Cable
 - 2500 lb. -- holds 2000' of 3/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Hybrid Option Available
- Front Outrigger & Wire Winder options
- 2 Part Block and 7 Ton hook



7X3

10-TON PUMP HOIST

7X3 Specs

Mounted on Flatbed or Service Body

Standard Features

- 21,000 lb. Hook load on 3-part line (Block NOT included)
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/7,000 lbs.
 - Supplied with 250' of 7/16" cable & 5t hook
- 40 ft hydraulically extending MAST
 - Optional Extension up to 48'
- Standard 20 ft aluminum pipe racks with pipe securing winches
 - Hydraulic lowering option available
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- 50 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 1000 lb. -- holds 1000' of 3/8" Cable
 - 1500 lb. -- holds 1500' of 3/8" Cable
 - 2500 lb. -- holds 2000' of 3/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Hybrid Option Available
- Front Outrigger & Wire Winder options
- 3 Part block and 12 Ton Hook

9X3



15-TON PUMP HOIST

9X3 Specs

Mounted on Flatbed or Service Body

Standard Features

- 27,000 lb. Hook load on 3-part line (Block NOT Included)
- Variable Speed Main & Sand line
- Main & Sand line along with structure are tested and certified with Dynamometer
- NO GUIDE CABLE NEEDED
- Main Line pulls at 210 fpm/9,000 lbs.
 - Supplied with 250' of 1/2" cable & 5t hook
- 40 ft hydraulically extending MAST
 - Optional Extension up to 48'
- Standard 20 ft aluminum pipe racks with pipe securing winches
 - Hydraulic lowering option available
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 12' Diamond Plate Flatbed
- Custom Headache rack above deck
- 50 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 1000 lb. -- holds 1000' of 3/8" Cable
 - 1500 lb. -- holds 1500' of 3/8" Cable
 - 2500 lb. -- holds 2000' of 3/8" Cable
 - 3500 lb. -- holds 2500' of 1/2" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Hybrid Option Available
- Front Outrigger & Wire Winder options
- 3-Part Block



15X3

22-TON PUMP HOIST

15X3 Specs

Mounted on Flatbed

Standard Features

- 45,000 lb. Hook load on 3-part block
 - Variable Speed Main & Sand line
 - Main & Sand line along with structure are tested and certified with Dynamometer
 - NO GUIDE CABLE NEEDED
- Main Line pulls at 210 fpm/15,000 lbs.
 - Supplied with 250' of 5/8" cable & 10t hook
- 51 ft hydraulically extending MAST
 - 48' of True Hook Height
 - Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 16' Diamond Plate Flatbed
- Custom Headache rack above deck
- 85 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 3-Part Block

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 3500 lb. -- holds 2500' of 1/2" Cable
 - 5000 lb. -- holds 3500' of 1/2" Cable
 - 8000 lb. -- holds 4000' of 5/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Layout Line winches -- available on driver and/or passenger side
 - 250 fpm/2000 lb. -- 150' 3/8" Cable
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Cathead with rollers
- Sargent GEN 2 Spinner
 - 2-12" Pipe
 - Heavy Duty Clamp

20X3



30-TON PUMP HOIST

20X3 Specs

Mounted on Flatbed

Standard Features

- 60,000 lb. Hook load on 3-part block
 - Variable Speed Main & Sand line
 - Main & Sand line along with structure are tested and certified with Dynamometer
 - NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/20,000 lbs.
 - Supplied with 250' of 5/8" cable & 10t hook
- 53 ft hydraulically extending MAST
 - 51' of True Hook Height
 - Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 16' Diamond Plate Flatbed
- Custom Headache rack above deck
- 85 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 3-Part Block

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 3500 lb. -- holds 2500' of 1/2" Cable
 - 5000 lb. -- holds 3500' of 1/2" Cable
 - 8000 lb. -- holds 4000' of 5/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Layout Line winches -- available on driver and/or passenger side
 - 250 fpm/2000 lb. -- 150' 3/8" Cable
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Cathead with rollers
- Sargent GEN 2 Spinner
 - 2-12" Pipe
 - Heavy Duty Clamp

25X4



50-TON PUMP HOIST

25X4 Specs

Mounted on Flatbed

Standard Features

- 100,000 lb. Hook load on 4-part block
 - Variable Speed Main & Sand line
 - Main & Sand line along with structure are tested and certified with Dynamometer
 - NO GUIDE CABLE NEEDED
- Main Line pulls at 200 fpm/25,000 lbs.
 - Supplied with 250' of 5/8" cable & 15t hook
- 55 ft hydraulically extending MAST
 - 53' of True Hook Height
 - Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 22' Diamond Plate Flatbed
- Custom Headache rack above deck
- 125 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST & BED
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 4-Part Block

Additional Options

- Sand Line Options – All 550 fpm bare drum
 - 3500 lb. – holds 2500' of 1/2" Cable
 - 5000 lb. – holds 3500' of 1/2" Cable
 - 8000 lb. – holds 4000' of 5/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Layout Line winches – available on driver and/or passenger side
 - 250 fpm/2000 lb. --150' 3/8" Cabel
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM/85 CFM/125 CFM Options
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line Bed Liner
- Cathead with rollers
- Sargent GEN 2 Spinner
 - 2-12" Pipe
 - Heavy Duty Clamp

30X4



60-TON PUMP HOIST

30X4 Specs

Mounted on Flatbed

Standard Features

- 120,000 lb. Hook load on 4-part block
 - Variable Speed Main & Sand line
 - Main & Sand line along with structure are tested and certified with Dynamometer
 - NO GUIDE CABLE NEEDED
- Main Line pulls at 220 fpm/30,000 lbs.
 - Supplied with 280' of 3/4" cable & 15t hook
- 55 ft hydraulically extending MAST
 - 53' of True Hook Height
 - Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 20' Diamond Plate Flatbed
- Custom Headache rack above deck
- 125 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 4-Part Block

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 3500 lb. -- holds 2500' of 1/2" Cable
 - 5000 lb. -- holds 3500' of 1/2" Cable
 - 8000 lb. -- holds 4000' of 5/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Layout Line winches -- available on driver and/or passenger side
 - 250 fpm/2000 lb. -- 150' 3/8" Cabel
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Cathead with rollers
- Sargent GEN 2 Spinner
 - 2-12" Pipe
 - Heavy Duty Clamp



35X4

70-TON PUMP HOIST

35X4 Specs

Mounted on Flatbed

Standard Features

- 140,000 lb. Hook load on 4-part block
 - Variable Speed Main & Sand line
 - Main & Sand line along with structure are tested and certified with Dynamometer
 - NO GUIDE CABLE NEEDED
- Main Line pulls at 210 fpm/35,000 lbs.
 - Supplied with 280' of 7/8" cable & 20t hook
- 58 ft hydraulically extending MAST
 - 55' of True Hook Height
 - Hydraulic extension by dual 15' Stroke Cylinders
- 4 Hydraulic Outriggers with 24" stroke 12" base
- Automatic Transmission PTO & Pump Installation
- Custom HD 8' x 20' Diamond Plate Flatbed
- Custom Headache rack above deck
- 125 Gallon aluminum oil tank
- Dual Custom mud flaps
- 6" LED lights on MAST
- Hydraulic cooler with thermostat control
- Dupont Imron 2-part industrial paint
- 4-Part Block

Additional Options

- Sand Line Options -- All 550 fpm bare drum
 - 3500 lb. -- holds 2500' of 1/2" Cable
 - 5000 lb. -- holds 3500' of 1/2" Cable
 - 8000 lb. -- holds 4000' of 5/8" Cable
 - Adjustable speed settings
 - Available counter that shows DEPTH in INCHES
- Layout Line winches -- available on driver and/or passenger side
 - 250 fpm/2000 lb. -- 150' 3/8" Cabel
- Electric over Hydraulic Upgrade
 - Electronic oil pressure gauge
 - Electronic oil temperature
 - Electronic oil filter service indicator
 - Weight Load Indicator in LBS.
 - Wireless Remote
 - Controls MAST, throttle, Main & Sand Line from up to 300 ft. away
- JoMac Custom Tool Boxes
 - Sealed airtight with locks
- GETEC Hydraulic Generator
 - 120V/14,000 Watts
- Hydraulic Air Compressor
 - 17 CFM
- Auxillary Hydraulics/Breakout Cylinder
- Rhino Line
- Cathead with rollers
- Sargent GEN 2 Spinner
 - 2-12" Pipe
 - Heavy Duty Clamp